

# LOW COST AUTOMATED PLASMA CLEANER



WITH AN INCREDIBLY LOW STARTING PRICE, THE PLASMA ETCH, INC.
PE-25-JW IS A HIGH QUALITY PLASMA CLEANER THAT PRODUCES CONSISTENT, REPEATABLE RESULTS.

THIS USER-FRIENDLY SYSTEM HAS AUTOMATIC PROCESS SEQUENCING CAPABILITIES, AND ALL TIMED EVENTS (PUMPDOWN, PLASMA, GAS STABILIZATION AND VENT) CAN BE EASILY PROGRAMMED INTO THE AUTOMATIC SEQUENCE. THE PLC KEYPAD IS USED FOR OPERATOR ENTRY, AND ONE COMPLETE PROCESS RECIPE CAN BE STORED IN MEMORY.

AS IN ALL PLASMA ETCH SYSTEMS, DIRECT RF CONTACT (CAPACITIVE PARALLEL PLATE) IS USED FOR UNIFORM PLASMA GENERATION. THIS UNIT HAS A 150W 50KHZ RF POWER SUPPLY WITH CONTINUOUSLY VARIABLE POWER CAPABILITY, THE SYSTEM COMES WITH A 3.5" X 7" HORIZONTAL "DIRECT CONTACT" RF POWERED ELECTRODE WITH 2.5" OF CHAMBER HEIGHT CLEARANCE. EQUIPPED WITH PLC CONTROL, THIS SYSTEM COMES WITH A SINGLE GAS CHANNEL AND HAS THE OPTION OF A SECOND CHANNEL. IT IS FULLY AUTOMATED WITH AN ALUMINUM CHAMBER.

THE PE-25-JW IS OUR LOWEST PRICED PLASMA CLEANER, MADE FOR SMALLER PRODUCTION FACILITIES, RESEARCH AND DEVELOPMENT LABS, TESTING FACILITIES, UNIVERSITIES, AND IS GREAT FOR PLASMA STERILIZATION AND SURFACE MODIFICATION.

# PLASMA ETCH

3522 ARROWHEAD DRIVE CARSON CITY, NV 89706 775.883.1336 www.PLASMAETCH.COM SALES@PLASMAETCH.COM





## STANDARD SYSTEM FEATURES

WELDED ALUMINUM VACUUM CHAMBER, 5" X 8" DEEP
SINGLE 3.5" X 7" HORIZONTAL ELECTRODE
150 WATTS @ 50 KHz R.F. GENERATOR; OPTIONAL 400 WATT POWER SUPPLY.
PRECISION NEEDLE VALVE FLOW CONTROL 0-25 CC/MIN
THERMOCOUPLE VACUUM GAUGE, 0-1 TORR
AUTOMATED PLC MICROPROCESSOR

### OPTIONAL SYSTEM FEATURES

2ND ROTOMETER, 2ND GAS CONTROL, 0-25CC/MIN W/PRECISION NEEDLE VALVE
5 CFM 2-STAGE DIRECT DRIVE OIL VACUUM PUMP, OXYGEN SERVICE (KRYOX CHARGED)

#### SYSTEM ELECTRICAL & MECHANICAL

CONSOLE DIMENSIONS: 14"W x 14.5"D x 18"H

SHIPPING WEIGHT APPROXIMATELY 52LBS

ELECTRICAL; 120VAC, 15A

775.883.1336

WWW.PLASMAETCH.COM

3522 ARROWHEAD DRIVE CARSON CITY NV. 89706

